

CLAMP DEVICE

Invented by

Daniel L. Poole

a resident of

3319 West Malapai Drive  
Phoenix, Arizona 85051

and

Robert N. Poole

a resident of

39820 North Seventh Street  
Phoenix, Arizona 85027

both citizens of  
the United States

PHOENIX, ARIZONA

1 CLAMP DEVICE

2

3 This application claims the benefit of U.S.  
4 Provisional Application 60/132,266, filed 03 May 1999.

5

6 FIELD OF THE INVENTION

7

8 This invention relates generally to clamping devices,  
9 and more particularly to clamping devices which can be  
10 manipulated with one hand.

11

12 BACKGROUND OF THE INVENTION

13

14 Clamping devices are well known and have been in use  
15 for many years. Particularly, straight bar friction  
16 locking clamps are extremely popular. These clamp devices  
17 can be operated one handed, and are very effective. The  
18 problem with these devices is that they operate in a linear  
19 fashion, with the clamping jaws sliding directly toward and  
20 away from one another. This structure presents some  
21 limitations such as limiting access of the clamp in tight  
22 spots, etc.

1        Often, pliers are used to clamp items together because  
 2        the motion of the handles permits their use in closer  
 3        spaces.    The problem with pliers is that the user must  
 4        maintain the pressure on the handles, as they do not remain  
 5        locked in position.    Locking pliers using friction locks  
 6        have been introduced, but while they will lock into a  
 7        specific configuration, they will not clamp unless the  
 8        material to be clamped is resilient.    When rigid items are  
 9        to be clamped, the clamping jaws will close to the surface  
 10       of the item but will not hold it securely.

11

12        Accordingly, it would be highly desirable to provide  
 13        an improved clamp device.

14

15        It is a purpose of the present invention to provide a  
 16        clamp device which can be operated with one hand.

17

18        It is another purpose of the present invention to  
 19        provide a clamp device which will securely hold a rigid  
 20        item.

21

22        It is still another purpose of the present invention  
 23        to provide a clamp device with a release trigger which  
 24        remains in position.

1        It is a further purpose of the present invention to  
2 provide a clamp device which can be operated in confined  
3 spaces.

SECRET-RESTRICTED

Summary of the Invention

The above problems and others are at least partially solved and the above purposes and others are realized in a clamp device. The clamp device includes a first member and a second member, each having a handle portion and a jaw portion. The jaw portions and/or the handle portions are flexible in an outward direction and biased in an inward direction for the jaw portion and the reverse for the handle portions. A pivot pivotally couples the first member and the second member intermediate their respective handle portion and jaw portion for opposed pivotal motion between an open position and a closed position. Also provided is a locking assembly having a frictionally engaged position, preventing the first member and the second member from moving toward the open position and a disengaged position allowing the first member and the second member to move toward the open position.

In specific embodiments the locking assembly includes an arcuate clamp bar having a first end coupled to the first member and a second end. An arc of the arcuate clamp bar is concentric with the pivot. Also provided is a <sup>brake</sup> ~~break~~ lever having an end pivotally coupled to the second member

1 and having an aperture with the arcuate clamp bar extending  
2 therethrough. The ~~break~~<sup>brake</sup> lever is movable laterally between  
3 the frictionally engaged position, frictionally engaging  
4 the arcuate clamp bar, and the disengaged position, and is  
5 substantially motionless longitudinally.

BRIEF DESCRIPTION OF THE DRAWINGS

Specific objects and advantages of the instant invention will become readily apparent to those skilled in the art from the following detailed description of a preferred embodiment thereof taken in conjunction with the drawings, in which:

FIG. 1 is a perspective view of a clamp device in accordance with the present invention, hidden portions illustrated in broken lines for clarity;

FIG. 2 is a plan view of a snap-on jaw portion broken away to illustrate pivotal movement;

FIG. 3 is a plan view of a clamp bar of the clamp device of FIG. 1;

FIG. 4 is a side elevational view of a brake lever of the clamp device of FIG. 1;

FIG. 5 is a plan view of the clamp device of FIG. 1 with the brake lever in an inoperative mode, portions thereof broken away;

1        FIG. 6 is a plan view of the clamp device of FIG. 1 as  
2   it appears in the closed position, hidden portions  
3   illustrated in broken lines for clarity;

4

5        FIG. 7 is a plan view of another embodiment of a clamp  
6   device in the closed position according to the present  
7   invention, hidden portions illustrated in broken lines for  
8   clarity;

9

10       FIG. 8 is a plan view of a clamp bar of the clamp  
11   device of FIG. 7;

12

13       FIG. 9 is a side elevational view of a brake lever of  
14   the clamp device of FIG. 7;

15

16       FIG. 10 is a perspective view of the clamp device of  
17   FIG. 7 as it appears in an open position, hidden portions  
18   illustrated in broken lines for clarity;

19

20       FIG. 11 is a perspective view of another embodiment of  
21   a clamp device according to the present invention;



1           FIG. 12 is a perspective view of yet another  
2 embodiment of a clamp device according to the present  
3 invention; and

5           FIG. 13 is a plan view of a further embodiment of a  
6 clamp device according to the present invention.

1 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

2  
3  
4 Turning now to the drawings in which like reference  
5 characters indicate corresponding elements throughout the  
6 several views, attention is first directed to FIG. 1, which  
7 illustrates a clamp device generally designated 20. Clamp  
8 device 20 includes a pair of members 22 and 23 pivotally  
9 connected by a pivot 24 (bolt, rivet, screw, etc.) for  
10 pivotal opposed operation (i.e. scissors like motion).  
11 Member 22 includes a handle portion 25 and a jaw portion 26  
12 generally determined by pivot 24. Similarly, member 23  
13 includes a handle portion 27 and a jaw portion 28 generally  
14 determined by pivot 24. <sup>B<sub>1</sub></sup> The distal end of jaw portion 26  
15 has a snap-on gripping member 30 pivotally coupled thereto  
16 (see FIG. 2 for pivotal action). The distal end of jaw  
17 portion 28 has a snap-on gripping member 31 pivotally  
18 coupled thereto (illustrated in an unsnapped position for  
19 clarity). Included in this embodiment is an optional  
20 spring 35 which is carried by pivot 24 with outwardly  
21 extending ends which engage handle portions 25 and 27 to  
22 bias clamp device 20 into the open position illustrated in  
23 FIG. 1. Spring 35 can be omitted allowing clamp device 20

1 to be operated similar to conventional pliers with manual  
2 opening and closing.

3

4 In accordance with the present invention, clamp device  
5 20 further has a locking assembly 40 including a clamp bar  
6 42 and a brake lever 43. Clamp bar 42 is an elongate  
7 arcuate design (see FIG. 3) with a coupled end 44 pivotally  
8 attached to handle portion 25 by a roll pin 45 (or any  
9 convenient mechanism to allow limited movement) permitting  
10 relative pivotal movement. A free end 46 of clamp bar 42  
11 extends unhindered through or adjacent to handle portion  
12 27, allowing free relative movement of handle portions 25  
13 and 27. It should be understood that clamp bar 42 can be  
14 received in a groove or aperture 50 formed in handle  
15 portion 27. It should also be understood that clamp bar 42  
16 has an arcuate shape to correspond to the pivotal movement  
17 of elements 22 and 23, and is positioned to be  
18 substantially parallel to pivot 24, i.e. the arc of clamp  
19 bar 42 is concentric with pivot 24. However, slight  
20 variation will still operate.

21

22 Brake lever 43 has an aperture 52 formed therethrough  
23 proximate a pivotal end 53. Clamp bar 42 is slideably  
24 received through aperture 52 with pivotal end 53 of brake

1 lever 43 pivotally engaged in a notch 54 formed in handle  
 2 portion 27 proximate pivot 24. A compression spring 55 is  
 3 positioned between brake lever 43 and handle portion 27 so  
 4 as to bias brake lever 43 outwardly away from handle  
 5 portion 27 and frictionally engage clamp bar 42 at aperture  
 6 52. Brake lever 43 is moveable between a frictionally  
 7 engaged (locking) position and a disengaged position. In  
 8 the frictionally engaged position brake lever 43  
 9 frictionally engages clamp bar 42 preventing movement  
 10 thereof and thereby preventing opening of clamp device 20  
 11 without preventing the closing thereof, i.e. locking  
 12 assembly 40 prevents clamp device 20 from opening but  
 13 allows it to be closed or clamped to an object. Here it  
 14 should be noted that spring 55 normally biases brake lever  
 15 43 into the frictionally engaged (locked) position (as  
 16 illustrated in FIG. 1). In the disengaged position brake  
 17 lever 43 has been moved toward handle portion 27 against  
 18 the bias of spring 55 removing the frictional engagement  
 19 between brake lever 43 and clamp bar 42, permitting clamp  
 20 bar 42 to move freely through aperture 52. Thus, clamp  
 21 device 20 can be opened. A latch 60 is slideably mounted  
 22 in handle portion 27 so as to be selectively engagable with  
 23 a free end 61 of brake lever 43, holding brake lever 43 in  
 24 the disengaged position (see FIG. 5) and able to operate as

1 conventional pliers. Turning to FIG. 6, clamp device 20 is  
2 shown in a closed position. Because the curvature of clamp  
3 bar 42 is concentric with pivot 24, break lever 43 does not  
4 move longitudinally. This permits the use of latch 60 and  
5 aperture 52 more closely sized to match the width of clamp  
6 bar 42.

7

8 Referring now to FIGS. 7-10, another embodiment of  
9 clamp device generally designated 120 is illustrated.  
10 Clamp device 120 includes a pair of members 122 and 123  
11 pivotally connected by a pivot 124 (bolt, rivet, screw,  
12 etc) for pivotal opposed operation (i.e. scissors like  
13 motion). Member 122 includes a handle portion 125 and a  
14 jaw portion 126 generally determined by pivot 124.  
15 Similarly, member 123 includes a handle portion 127 and a  
16 jaw portion 128 generally determined by pivot 124. The  
17 distal end of jaw portion 126 preferably has a snap-on  
18 gripping member 130 pivotally coupled thereto although this  
19 may be omitted. The distal end of jaw portion 128 has a  
20 snap-on gripping member 131 pivotally coupled thereto  
21 although this may be omitted if gripping member 130 is  
22 omitted. Included in this embodiment is an optional spring  
23 135 which is carried by pivot 124 with outwardly extending  
24 ends which engage handle portions 125 and 127 to bias clamp

1 device 120 into the open position illustrated in FIG. 10.  
2 Spring 135 can be omitted allowing clamp device 120 to be  
3 operated similar to conventional pliers with manual opening  
4 and closing.

5

6 In accordance with the present invention, clamp device  
7 120 further has a locking assembly 140 including a clamp  
8 bar 142 and a brake lever 143. Clamp bar 142 is an  
9 elongate arcuate design (see FIG. 8) with a coupled end 144  
10 pivotally attached to handle portion 125 by a roll pin 145  
11 (or any convenient mechanism to allow limited movement)  
12 permitting relative pivotal movement to insure  
13 concentricity of the arc to pivot 124. A free end 146 of  
14 clamp bar 142 extends unhindered through or adjacent to  
15 handle portion 127, allowing free relative movement of  
16 handle portions 125 and 127. In this specific embodiment,  
17 handle portion 127 is hollow, and a pair of parallel spaced  
18 apart roll pin guides 156 contained therein receive clamp  
19 bar 142 slideably therebetween. In this fashion, instead  
20 of clamp bar 142 extending beyond the handle in the closed  
21 position it is contained within the hollow and thickened  
22 handle portion 127.

1 Brake lever 143 has an aperture 152 formed  
2 therethrough proximate a pivotal end 153. In this  
3 embodiment, aperture 153 has rounded ends which correspond  
4 to rounded edges of clamp bar 142. This provides greater  
5 frictional engagement therebetween. Clamp bar 142 is  
6 slideably received through aperture 152 with pivotal end  
7 153 of brake lever 143 pivotally engaged in a notch 154  
8 formed in handle portion 127 proximate pivot 124. A  
9 compression spring 155 is positioned between brake lever  
10 143 and handle portion 127 so as to bias brake lever 143  
11 outwardly away from handle portion 127 and frictionally  
12 engage clamp bar 142 at aperture 152. Brake lever 143 is  
13 moveable between a frictionally engaged (locking) position  
14 and a disengaged position. In the frictionally engaged  
15 position brake lever 143 frictionally engages clamp bar 142  
16 preventing movement thereof and thereby preventing opening  
17 of clamp device 120. Here is should be noted that spring  
18 155 normally biases brake lever 143 into the frictionally  
19 engaged position (as illustrated in FIG. 7 and 10). In the  
20 disengaged position brake lever 143 has been moved toward  
21 handle portion 127 against the bias of spring 155  
22 permitting clamp bar 142 to move freely through aperture  
23 152. While a latch is not shown in this embodiment, it is  
24 optional in all embodiments.

1        In each of the previously described embodiments, clamp  
 2 devices 20 and 120 are preferably formed of a flexible  
 3 material such as plastic. While rigid materials such as  
 4 metal may be employed, the clamping operation will not be  
 5 as effective unless the metal is flexible. By flexing in  
 6 an outward direction under pressure from the item being  
 7 clamped, the jaw portions of members 22 and 23 of device 20  
 8 and members 122 and 123 of device 120 form a tension system  
 9 which permits a tight clamping action by their bias in the  
 10 inward direction. In the same manner, the handle portions  
 11 of the members flex in an inward direction as compression  
 12 is applied, and bias outwardly upon release of the  
 13 compression force, placing pressure upon the jaw portions.

14  
 15        Turning now to FIG. 11, a further embodiment of a  
 16 clamp device generally designated 220 is illustrated.  
 17 Device 220 is substantially similar to devices 20 and 120,  
 18 and in fact can be identical with the addition of clip  
 19 springs 202 and 203 attached to members 222 and 223 at the  
 20 distal ends of jaw portions 226 and 228 respectively.  
 21 Thus, members 222 and 223 can be formed of a rigid material  
 22 such as steel having no flex, with the flex provided by  
 23 spring clips 202 and 203. In this manner a tension system  
 24 providing a strong clamping action is achieved. However,



1 in this embodiment, clips 202,203 can be removed. Clamp  
2 device 220 can be constructed of a resilient and flexible  
3 material such as spring steel. In this manner, jaw  
4 portions 226 and 228 can form a tension system as  
5 previously described. Furthermore, members 222 and 223  
6 include handle portions 225 and 227, respectively. Handle  
7 portions 225 and 227 can also be formed of a flexible and  
8 resilient material. To enhance the flexibility, the  
9 handles can be hollowed as shown. This provides the  
10 flexibility and shape memory required to form a tension  
11 system as described previously.

13 Referring to FIG. 12, another embodiment of a clamping  
14 device generally designated 320 is illustrated. Again,  
15 device 320 is substantially identical to the previously  
16 described embodiments, including a pair of members 322 and  
17 323 pivotally connected by a pivot 324 (bolt, rivet, screw,  
18 etc) for pivotal opposed operation (i.e. scissors like  
19 motion). Member 322 includes a handle portion 325 and a  
20 jaw portion 326 generally determined by pivot 324.  
21 Similarly, member 323 includes a handle portion 327 and a  
22 jaw portion 328 generally determined by pivot 324. A flex  
23 in members 322 and 323 is provided by a pivot joint 302  
24 formed in jaw portion 326. The slight pivot is biased by

1 compression spring 303 carried at pivot joint 302 to force  
 2 the distal ends of jaw portions 326 and 328 toward one  
 3 another in an inward direction. During a clamping  
 4 operation, as jaw portions 326 and 328 are brought toward  
 5 one another into contact with an item to be clamped, the  
 6 terminal ends are moved outward against the bias of spring  
 7 303 bringing the whole structure under tension and forming  
 8 a strong clamping action. It should be understood that a  
 9 pivot joint and compression spring can also be installed on  
 10 jaw portion 328.

11  
 12 With reference to FIG. 13, another embodiment of a  
 13 clamp device generally designated 420 is illustrated.  
 14 Clamp device 420 is substantially identical to the previous  
 15 embodiments, including a pair of members 422 and 423  
 16 pivotally connected by a pivot 424 (bolt, rivet, screw,  
 17 etc.) for pivotal opposed operation (i.e. scissors like  
 18 motion). Member 422 includes a handle portion 425 and a  
 19 jaw portion 426 generally determined by pivot 424.  
 20 Similarly, member 423 includes a handle portion 427 and a  
 21 jaw portion 428 generally determined by pivot 424. Clamp  
 22 device 420 further has a locking assembly 440 including a  
 23 clamp bar 442 and a brake lever 443. The difference  
 24 between this embodiment and previous embodiments, is that

1 jaw portions 426 and 428 are coupled to handle portions 425  
2 and 427 at substantially right angles thereto. Thus the  
3 jaws portions extend substantially perpendicularly from  
4 pivot 424 with respect to the handle portions. Any of the  
5 variously disclosed tension systems may be employed in  
6 clamp device 420.

7

8 Various changes and modifications to the embodiments  
9 herein chosen for purposes of illustration will readily  
10 occur to those skilled in the art. For example, while the  
11 arcuate clamp bars are illustrated coupled at one end by a  
12 pin, it will be understood that the clamp bars may be  
13 coupled by being integrally formed with one of the handle  
14 portions, adhered thereto or welded, etc. To the extent  
15 that such modifications and variations do not depart from  
16 the spirit of the invention, they are intended to be  
17 included within the scope thereof which is assessed only by  
18 a fair interpretation of the claims.

19

20 Having fully described the invention in such clear and  
21 concise terms as to enable those skilled in the art to  
22 understand and practice the same, the invention claimed is: